

4

# TECHNICAL PROGRESS REPORT #3

A compact programmable laser Doppler velocimeter for marine applications

Contract Number 90-C-0105

AD-A228 736

## Prepared for:

Dr. Joseph H. Kravitz  
Office of Naval Research  
800 N. Quincy Street  
Arlington, Virginia 22217

## Prepared by:

Dr. Cecil F. Hess  
MetroLaser  
18006 Skypark Circle Suite 108  
Irvine, CA 92714

DTIC  
ELECTE  
OCT 22 1990  
S B D

DISTRIBUTION STATEMENT A  
Approved for public release;  
Distribution Unlimited

### TECHNICAL PROGRESS REPORT #3

#### Introduction

The three major tasks conducted during this period are the completion of the construction of a small water test section, the testing of the electronic processor, and the successful acquisition of single and two-velocity component LDV data. The test section consists of a rectangular Plexiglass section with a nozzle on one end and an extraction orifice on the other. A recirculating pump and flexible tubing are used to draw water from a reservoir, flow it through the test section and return it to the reservoir. Polystyrene particles of  $10\text{ }\mu\text{m}$  in diameter were seeded into the flow. The laser beams were oriented to measure both the horizontal and vertical velocity components. The test section could be oriented at arbitrary angles to the incoming laser beams to produce flows at arbitrary directions.

#### Discussion

The system uses a 40 mW diode laser operating at 805 nm, three Bragg cells which provide frequency shifting, and a programmable digital signal processor (DSP) which will lead to a autonomous system capable of intelligent decisions. For stationary particles, the horizontal velocity component has a frequency shift ( $fs_1$ ) of 5 MHz and the vertical velocity component has a frequency shift ( $fs_2$ ) of 10 MHz. Thus, when the particles move due to flow velocity, the processed frequencies would be:

$$f_1 = fs_1 \pm U/\delta_1, \quad (1)$$


$$f_2 = fs_2 \pm V/\delta_2, \quad (2)$$

where  $f_1$  and  $f_2$  are the processed frequencies,  $\delta_1$  and  $\delta_2$  are the fringe spacings, and  $U$  and  $V$  are the velocity components in the horizontal and vertical directions. The values of  $\delta_1$  and  $\delta_2$  are  $28\text{ }\mu\text{m}$  and  $25\text{ }\mu\text{m}$  respectively.

The two enclosed graphs show the processed frequency both in the time domain and the frequency domain. The frequency spectrum was obtained by performing an FFT on the collected data. Notice the values of  $f_1 = 5.225\text{ MHz}$  and  $f_2 = 10.25\text{ MHz}$ . Substituting these values into equations (1) and (2), we arrive with velocity values of  $U = V = 6.2\text{ m/s}$ . In this particular example the  $U$  and  $V$  components are equal and correspond to flow moving at 45 degrees. In general,  $U$  and  $V$  can have arbitrary values. This arrangement permits the measurement of flow velocity and turbulence at arbitrary directions; including recirculating flows.



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By <i>See ADA226266</i>	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<i>A-1</i>	




Simulation Mode Offset=72 Tr Level=45

Blk=0 Strt Byte=1 Length=1024

F1-Help F2-Options F3-Message F4-New Data F5-Change Color filter OFF  
 F6-Setup Table F7-Time/Freq F8-Con Trig F9-Refresh F10-Exit dScope

6.25 u/dio



Simulation Mode Offset=72 Tr Level=45

Blk=0 Strt Byte=1 Length=2048

F1-Help F2-Options F3-Message F4-New Data F5-Change Color filter OFF  
F6-Setup Table F7-Time/Freq F8-Con Trig F9-Refresh F10-Exit dScope